

TECHNOLOGY BRIEF:

Ultra-high shear rotor/stator systems speed up cycle time by reducing the number of passes required through a high pressure homogenizer, an inherently low-throughput, high-energy device. Since homogenizers are also generally maintenance-intensive, an efficient ‘pre-mixer’ generates significant savings in the overall cost of production. In certain applications, ultra-high shear mixers even offer a viable alternative to homogenizers.

Ultra-high shear mixers increase overall throughput and efficiency of homogenization processes.



Maximizing process efficiency during pre-mixing

Many fine emulsions and dispersions require multiple passes through a high pressure homogenizer to achieve the final droplet or particle size distribution. Operating and maintenance costs for a homogenizer are comparatively high, so the addition of an upstream mixer that can prepare a finer premix and reduce the number of passes through the homogenizer significantly reduces processing costs and sharply improves equipment utilization.

Ultra-high shear mixers vs. conventional rotor/stators

Several types of mixing systems are utilized for combining raw materials into a pre-mix. There are gentle agitation devices such as low speed propellers, turbines or paddle agitators. Better quality pre-mixes are achieved through the use of high speed devices like open-disc saw-tooth blades and high shear rotor/stator mixers. Conventional high shear mixers feature a four-blade rotor running at tip speeds in the range of 3,000-4,000 feet/min within a close tolerance fixed stator. This type of device creates mechanical and hydraulic shear by continuously drawing product components into the rotor and expelling them radially through the openings in the stator. Ultra-high shear mixers, on the other hand, operate at much higher tip speeds around

Continued on page 2

Ultra-High Shear Mixer Rotor/Stator Designs



X-Series

US Patent No. 5,632,596



QuadSlot



MegaShear

US Patent No. 6,241,472

11,000– 18,000 fpm. The product being mixed is subjected to higher levels of shear compared to what is seen on conventional rotor/stator mixers.

Finer pre-mix, increased throughput

The high tip speeds and complex turbulent mixing patterns generated within the rotor/stator assembly of an ultra-high shear mixer enable it to produce fine emulsions and dispersions. The benefit of preparing a higher quality pre-mix lies in the reduction of passes through the high pressure homogenizer, an inherently low-throughput device. A greater volume of end product can therefore be produced per operating hour of the homogenizer. Being an inline device, the ultra-high shear mixer can mix raw materials and pump the mixture directly to the homogenizer. Flowrate is comparatively higher than a similarly powered homogenizer.

Viable alternative to high pressure homogenizers

In certain applications, ultra-high shear mixers even effectively replace high pressure homogenizers. These include submicron emulsions and dispersions, as well as formulations that degrade upon exposure to excessive shear.



Sample Application: Silicone Emulsion

A manufacturer of specialty coatings has standardized their silicone emulsion production on Ross X-Series Ultra-High Shear Mixers. The bold move from their previously established homogenization process was made after testing at the Ross Test & Development Center. The mixing trial confirmed that the X-Series produces the desired average droplet size and narrow distribution at a much higher throughput than their high pressure homogenizers. Easier maintenance and lower capital cost are the other reasons that this company's silicone emulsions are today being made on X-Series units installed in their various facilities.

